

# CELL POWER

## CESS 314-75

The CESS 314-75 has been developed for applications where flexibility and reliability are paramount. From grid reinforcement and peak shaving to charging hub buffering. With over 9,125 cycles and a 10-year warranty, this system delivers long-lasting performance. The CESS 314-75 is designed and manufactured in the Netherlands, drawing on 35 years of battery expertise. This results in a modular energy system with the highest energy density on the market, maximum safety, and a strong focus on cybersecurity. Thanks to local service and data management within Europe, the CESS 314-75 is the scalable choice for future-oriented energy projects.

35 +

### Developed in the Netherlands

Developed by a Dutch battery specialist with over 35 years of experience. Reliable, innovative, and close to home.



### Highest energy density

314 kWh storage capacity and 75 kW power in a compact unit measuring only 1.3 by 1.3 meters. Maximum energy, minimal space.



### Cybersecurity & Data security

All control and data processing take place in the Netherlands. The systems are extra secure thanks to a protected network. Your data remains safe.



### Local service and support

Focus on local services: from installation and maintenance to training. Our Dutch specialists are ready to assist you.



# CELL POWER

## CESS 314-75



### EXAMPLE CONFIGURATIONS

2 pcs	628 kWh - 150 kW
3 pcs	942kWh - 225 kW
4 pcs	1256 kWh - 300 kW
10 pcs	3135 kWh - 750 kW
x pcs in parallel maximum	Unlimited expandability

### GENERAL INFORMATION

Dimensions (LxWxH)	1300 x 1300 x 2374 mm
Weight	~3300kg
Housing	Outdoor cabinet
Anti corrosion level	C5
Noise level	≤75dB
Protection rating	IP55
Operating temperature	-30°C ~ +50°C
Relative humidity	20% ~ 85% (Non-condensing)
Maximum operating altitude	2000m (No derating)
Thermal management system	Liquid cooling
EMS integrations (multiplatform)	WithTheGrid, Covolt, Embion, Environ and more
Communication interface	MODBUS TCP
Off-grid capability	No

### BATTERY

Battery technology	LFP (LiFePO4/ Lithium Iron Phosphate)
Nominal Energy	313,5 kWh
Nominal Capacity	314 Ah
Nominal Voltage	998,4V
Voltage range (min. - Max.)	873,6V ~ 1107,6V
Cycle life @0.25C / 25°C	≥9125 cycles @90% D.o.D.; 70% EOL
DoD	100%

### INVERTER

Rated / nominal AC power	75 kW
Maximum AC power	75 kW
Grid voltage	400V
Grid voltage range	340V ~ 440V
AC current	109A
THD	≤1,5% v (100% Load)
AC power factor	-1 (Lagging) ~ 1 (Leading)
AC frequency	50/60Hz ± 5HZ
Max efficiency	98.3%
Round Trip Efficiency (RTE)	≥92%

### SAFETY

Fire suppression system	Double fire suppression system; battery pack Aerosol and cabinet
Detection systems	Smoke, temperature, water and humidity sensors (H2 optional)
Warning systems	Sound- and indicator alarms; alarm forwarding possible (PAC)

### WARRANTY & CERTIFICATE

Warrenty	10 years
Certificates battery	UN38.3; IEC 62619; UL 9540A; UL 1973
Certificates inverter	CE; IEC 61000-6-4; IEC 62477; EN 50549-1; EN 50549-2; VDE4105/4110/4120; TÖR A/B; Synergrid C10/11; G99; CEI 0-21