

Battery charger

LCP12015TAM

AGM battery charger (12 Volt)



Absorption charge Voltage Boost charge Current Recovery charge

Typical applications

- Mobility scooters
- Electric wheelchairs
- Electric vehicles
- E-bikes
- Lawn mowers
- Golfcarts
- Medical equipment
- Recreational vehicles

Features

- AGM battery charger
- Approved for medical applications
- 3-step intelligent charging
- · High efficiency
- For indoor use only

Nominal voltage	12 V
Battery capacity	6 - 15 Ah
Maximum charging current	1.5 A
Suitable for	AGM
Output connector	Tamia connector
Input voltage	100 - 240 V
Operational temperature range	0°C - +40°C
Dimensions Length	81 mm
Dimensions Width	53 mm
Dimensions Height	35 mm
Approximate Weight	0.15 kg
Packing	1 pcs/box
Technical features	Short circuit protection, protection
	against reverse polarity
Certifications	CE, UL
Standards	EN 60601-1:2006+A2:2021
	EN 60601-1-2:2015/A1:2021

Cellpower family

Cellpower supplies a broad range of reliable AGM, GEL and Lithium batteries. Each product series has its own unique characteristics, so that there is a suitable battery for every application with its associated specific usage profile. Combined with the right Cellpower battery accessories, you are able to assemble a high-quality and reliable battery system.

The Lithium batteries of Cellpower combine unparalleled cyclic performance with a light weight and compact dimensions. These advantages over AGM or GEL batteries make Lithium batteries a

very compelling choice for a wide range of applications. They offer more power for a longer period of time.

