

# CELL POWER

## CESS 366-160

The CESS 366-160 has been developed for applications where flexibility and reliability are paramount. From grid reinforcement and peak shaving to charging hub buffering and energy trading. With over 9,125 cycles and a 10-year warranty, this system delivers long-lasting performance. The CESS 366-160 is designed and manufactured in the Netherlands, drawing on 35 years of battery expertise. This results in a modular energy system with the highest energy density on the market, maximum safety, and a strong focus on cybersecurity. Thanks to local service and data management within Europe, the CESS 366-160 is the scalable choice for future-oriented energy projects.



### European quality and control

Controlled by our own software in a secure network. No external control or cloud data link outside the EU.



### Highest energy density

Maximum energy with minimal space.



### Highest safety level to even be placed indoors

Our systems have passed the UL9540A tests for thermal safety.



### Local service and support

Focus on local services: from installation and maintenance to training – our Dutch specialists are ready to assist you.



# CELL POWER

CESS 366-160



## EXAMPLE CONFIGURATIONS

2 pcs	732 kWh - 320 kW
3 pcs	942kWh - 480 kW
4 pcs	1464 kWh - 640 kW
10 pcs	3660 kWh - 1600 kW
x pcs in parallel maximum	Unlimited expandability

## GENERAL INFORMATION

Dimensions (LxWxH)	1300 x 1300 x 2374 mm
Weight	~3700kg
Housing	Outdoor cabinet
Anti corrosion level	C5
Noise level	≤75dB
Protection rating	IP55
Operating temperature	-20°C ~ +60°C
Relative humidity	0% ~ 100% (Non-condensing)
Maximum operating altitude	3000m (No derating)
Thermal management system	Liquid cooling
EMS integrations (multiplatform)	WithTheGrid, Covolt, Embion, Environ, Flexecharge, Eniris and more
Communication interface	MODBUS TCP
Off-grid capability	Yes

## BATTERY

Battery technology	LFP (LiFePO4/ Lithium Iron Phosphate)
Nominal Energy	313,5 kWh
Nominal Capacity	314 Ah
Nominal Voltage	998,4V
Voltage range (min. - Max.)	873,6V ~ 1107,6V
Cycle life @0.25C / 25°C	≥9125 cycles @90% D.o.D.; 70% EOL
DoD	100%

## INVERTER

Rated / nominal AC power	160kW (1200Vdc > derating to 90% 144kW)
Maximum AC power	176kVA discharging / 144kVA charging
Grid voltage	400V
Grid voltage range	340V ~ 460V
AC current	231A
THD	<3% v (100% Load)
AC power factor	-1 (Lagging) ~ 1 (Leading)
AC frequency	50/60Hz ± 5HZ
Max efficiency	98.3%
Round Trip Efficiency (RTE)	>92%

## SAFETY

Fire suppression system	Double fire suppression system; batterypack Aerosol and cabinet
Detection systems	Smoke, temperature, water and humidity sensors (H2 optional)
Warning systems	Sound- and indicator alarms; alarm forwarding possible (PAC)

## WARRENTY & CERTIFICATE

Warranty	10 years (5 years PCS)
Certificates battery	UN38.3; IEC 62619; UL 9540A; UL 1973
Certificates inverter	CE; EN 62109-1; EN62109-2; EN IEC 62477-1; EN IEC 61000-6-2; EN IEC 61000-6-4; EN 50549-1; EN50549-2; EN50549-10; VDR-AR-N 4110