

CELL POWER

CESS 366-90

The CESS 366-90 is developed for applications where flexibility and reliability are key. From grid reinforcement and peak shaving to charging hub buffering and energy trading. With over 9,125 cycles and a 10-year warranty, this system delivers long-lasting performance. The CESS 366-90 is developed in the Netherlands, based on 35 years of battery expertise. This results in a modular energy system with a high energy density, maximum safety, and a strong focus on cybersecurity. Thanks to local service and data management within Europe, the CESS 366-90 is the scalable solution for future-oriented energy projects.



European quality and control

Controlled by our own software in a secure network. No external control or cloud data link outside the EU.



Highest energy density in the market

Maximum energy with minimal space.



Highest safety level to even be Placed indoors

Our systems have passed the strict UL9540A test for thermal safety.



Local service and support

Focus on local services: from installation and maintenance to training – our Dutch specialists are ready to assist you.



CELL POWER

CESS 366-90



EXAMPLE CONFIGURATIONS

2 pcs	732 kWh - 180 kW
3 pcs	1098 kWh - 270 kW
4 pcs	1464 kWh - 360 kW
10 pcs	3660 kWh - 900 kW
x pcs in parallel maximum	Unlimited expandability

GENERAL INFORMATION

Dimensions (LxWxH)	1300 x 1300 x 2374 mm
Weight	~3700kg
Housing	Outdoor cabinet
Anti corrosion level	C5
Noise level	≤65dB at 2m
Protection rating	IP55
Operating temperature	-20°C ~ +60°C
Relative humidity	0% ~ 100% (Non-condensing)
Maximum operating altitude	3000m (No derating)
Thermal management system	Liquid cooling
EMS integrations (multiplatform)	WithTheGrid, Covolt, Embion, Environ, Flexecharge, Eniris and more
Communication interface	MODBUS TCP
Off-grid capability	Yes

BATTERY

Battery technology	LFP (LiFePO4/ Lithium Iron Phosphate)
Nominal Energy	365,75 kWh
Nominal Capacity	314 Ah
Nominal Voltage	1164,8V
Voltage range (min. - Max.)	1019,2V ~ 1292,2V
Cycle life @0.25C / 25°C	≥9125 cycles @95% D.o.D.; 70% EOL
DoD	95%

INVERTER

Rated / nominal AC power	90 kW
Maximum AC power	90 kVA
Grid voltage	400V
Grid voltage range	340V ~ 460V
AC current	231A
THD	≤3% v (100% Load)
AC power factor	-1 (Lagging) ~ 1 (Leading)
AC frequency	50/60Hz ± 5 HZ
Max efficiency	98.3%
Round Trip Efficiency (RTE)	≥92%

SAFETY

Fire suppression system	Double fire suppression system; batterypack Aerosol and cabinet
Detection systems	Smoke, temperature, water and humidity sensors (H2 optional)
Warning systems	Sound- and indicator alarms; alarm forwarding possible

WARRENTY & CERTIFICATE

Warrenty	10 years (5 years PCS)
Certificates battery	UN38.3; IEC 62619; UL 9540A; UL 1973
Certificates inverter	CE; IEC 61000-6-4; IEC 62477; EN 50549-1; EN 50549-2; VDE4105/4110/4120; TÖR A/B; Synergrid C10/11; G99; CEI 0-21